

View Online at <https://aerobasegroup.com/nsn/5950-00-011-6982>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.469 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 60.0 hertz single component

Input-output Phase Relationship:

Two phase to three phase single component

Body Length:

5.875 inches

Body Width:

4.625 inches

Body Height:

2.750 inches

End Application:

Forrestal class cv

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

100.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

81.00 ac volts single component 2nd primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0