

View Online at <https://aerobasegroup.com/nsn/5950-00-014-5742>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.438 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.750 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

4.125 inches

Body Width:

3.438 inches

Body Height:

3.920 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 9 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

530.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

8.30 ac volts single component 4th secondary and 300.00 ac volts single component 4th secondary

Special Features:

2 primary windings; 9 secondary windings

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

29 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0