

View Online at <https://aerobasegroup.com/nsn/5950-00-014-6425>

Reliability Indicator:

Not established

Transformer Function:

Line

Impedance Rating In Ohms:

87.5 single component single primary

Frequency Rating:

150.0 hertz single component and 15.0 kilohertz single component

Maximum Transformer Power Rating:

330.0 milliwatts single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.125 inches

Body Width:

1.085 inches

Body Height:

1.006 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

3 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

40 single group

Thread Size:

0.112 inches single group

Center To Center Distance Between Mounting Facilities Parallel To The Base Of An Isosceles Triangle:

0.800 inches single mounting facility single center group

Winding Operating Current:

125.0 milliamperes dc single component single primary

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

0.750 inches single mounting facility single center group

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0