

View Online at <https://aerobasegroup.com/nsn/5950-00-017-0525>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.980 inches single mounting facility single center group and 1.020 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.190 inches single mounting facility single center group and 0.230 inches single mounting facility single center group

Impedance Rating In Ohms:

10000.0 single component single primary

Frequency Rating:

400.0 hertz single component

Primary To Secondary Turn Ratio:

1 to 3 single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

1.400 inches

Body Width:

0.380 inches

Body Height:

1.210 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.112 inches single group

Test Data Document:

95750-54130560 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0