## NSN 5950-00-017-0533

Radio Frequency Coil - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-017-0533

Coil Form Type:Solid single componentBody Length:1.250 inchesBody Width:1.000 inchesBody Height:1.000 inchesDistance Between Mounting Facility Centers:0.562 inches single mounting facility single center groupInclosure Type:OpenMounting Facility Quantity:2 single groupMounting Method:Threade hole single groupThread Size:0.086 inches single groupWinding Operating Current:640.0 milliamperes ac single component single windingThread Sizeis Designator:Unc single groupFarminal Type And Quantity:1 tab, solder lug and 1 wire leadShelf Life:N/aUnit Of Measure:	
Body Length:1.250 inchesBody Width:1.000 inchesBody Height:1.000 inchesDistance Between Mounting Facility Centers:0.562 inches single mounting facility single center groupInclosure Type:OpenMounting Facility Quantity:2 single groupMounting Method:Threaded hole single groupThready Qty Per Inch (tpi):56 single groupMinding Operating Current:640.0 milliamperes ac single component single windingThread Size:Unc single groupThread Series Designator:Unc single groupTerminal Type And Quantity:1 tab, solder lug and 1 wire leadShelf Life:N/a	
1.250 inches Body Width: 1.000 inches Body Height: 1.000 inches Distance Between Mounting Facility Centers: 0.562 inches single mounting facility single center group Inclosure Type: 0.562 inches single mounting facility single center group Inclosure Type: 0pen Mounting Facility Quantity: 2 single group Mounting Method: 1 hreaded hole single group Thread hole single group Thread Size: 0.086 inches single group Minding Operating Current: 640.0 milliamperes ac single component single winding Thread Size: Unc single group Thread Size: 1 tab, solder lug and 1 wire lead Shelf Life: N/a	
Body Width:1.000 inchesBody Height:1.000 inchesDistance Between Mounting Facility Centers:0.562 inches single mounting facility single center groupInclosure Type:OpenMounting Facility Quantity:2 single groupMounting Method:Threaded hole single groupThreaded hole single groupS6 single groupMinding Operating Current:640.0 milliamperes ac single component single windingThread Series Designator:Unc single groupTerminal Type And Quantity:1 tab, solder lug and 1 wire leadShelf Life:N/a	
<ul> <li>1.000 inches</li> <li>Body Height: <ul> <li>1.000 inches</li> </ul> </li> <li>Distance Between Mounting Facility Centers: <ul> <li>0.562 inches single mounting facility single center group</li> </ul> </li> <li>Inclosure Type: <ul> <li>Open</li> </ul> </li> <li>Mounting Facility Quantity: <ul> <li>2 single group</li> </ul> </li> <li>Mounting Method: <ul> <li>Threaded hole single group</li> </ul> </li> <li>Thready Qty Per Inch (tpi): <ul> <li>56 single group</li> </ul> </li> <li>Minding Operating Current: <ul> <li>640.0 milliamperes ac single component single winding</li> <li>Thread Series Designator: <ul> <li>Unc single group</li> </ul> </li> <li>Terminal Type And Quantity: <ul> <li>1 tab, solder lug and 1 wire lead</li> <li>Shelf Life:</li> <li>N/a</li> </ul> </li> </ul></li></ul>	
Body Height: 1.000 inches Distance Between Mounting Facility Centers: 0.562 inches single mounting facility single center group Inclosure Type: Open Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Thready Qty Per Inch (tpi): 56 single group Thread Size: 0.086 inches single group Minding Operating Current: 640.0 milliamperes ac single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 1 tab, solder lug and 1 wire lead Shelf Life: N/a	
1.000 inches Distance Between Mounting Facility Centers: 0.562 inches single mounting facility single center group Inclosure Type: Open Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Thread hole single group Thready Qty Per Inch (tpi): 56 single group Thread Size: 0.086 inches single group Minding Operating Current: 640.0 milliamperes ac single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 1 tab, solder lug and 1 wire lead Shelf Life: N/a	
Distance Between Mounting Facility Centers:0.562 inches single mounting facility single center groupInclosure Type:OpenMounting Facility Quantity:2 single groupMounting Method:Threaded hole single groupThready Qty Per Inch (tpi):56 single groupThread Size:0.086 inches single groupWinding Operating Current:640.0 milliamperes ac single component single windingThread Series Designator:Unc single groupFarminal Type And Quantity:1 tab, solder lug and 1 wire leadShelf Life:N/a	
0.562 inches single mounting facility single center group Inclosure Type: Open Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Thread hole single group Thread Y Per Inch (tpi): 56 single group Thread Size: 0.086 inches single group Minding Operating Current: 640.0 milliamperes ac single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 1 tab, solder lug and 1 wire lead Shelf Life: N/a	
Inclosure Type: Open Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Thready Qty Per Inch (tpi): 56 single group Thread Size: 0.086 inches single group Minding Operating Current: 640.0 milliamperes ac single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 1 tab, solder lug and 1 wire lead Shelf Life: N/a	
Open Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Thready Qty Per Inch (tpi): 56 single group Thread Size: 0.086 inches single group Minding Operating Current: 640.0 milliamperes ac single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 1 tab, solder lug and 1 wire lead Shelf Life: N/a	
Mounting Facility Quantity:2 single groupMounting Method:Threaded hole single groupThready Qty Per Inch (tpi):56 single groupThread Size:0.086 inches single groupWinding Operating Current:640.0 milliamperes ac single component single windingThread Series Designator:Unc single groupTerminal Type And Quantity:1 tab, solder lug and 1 wire leadShelf Life:N/a	
2 single group Mounting Method: Threaded hole single group Thready Qty Per Inch (tpi): 56 single group Thread Size: 0.086 inches single group Winding Operating Current: 640.0 milliamperes ac single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 1 tab, solder lug and 1 wire lead Shelf Life: N/a	
Mounting Method: Threaded hole single group Thready Qty Per Inch (tpi): 56 single group Thread Size: 0.086 inches single group Winding Operating Current: 640.0 milliamperes ac single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 1 tab, solder lug and 1 wire lead Shelf Life: N/a	
Threaded hole single group Thready Qty Per Inch (tpi): 56 single group Thread Size: 0.086 inches single group Winding Operating Current: 640.0 milliamperes ac single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 1 tab, solder lug and 1 wire lead Shelf Life: N/a	
Thready Qty Per Inch (tpi): 56 single group Thread Size: 0.086 inches single group Winding Operating Current: 640.0 milliamperes ac single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 1 tab, solder lug and 1 wire lead Shelf Life: N/a	
56 single group Thread Size: 0.086 inches single group Winding Operating Current: 640.0 milliamperes ac single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 1 tab, solder lug and 1 wire lead Shelf Life: N/a	
Thread Size: 0.086 inches single group Winding Operating Current: 640.0 milliamperes ac single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 1 tab, solder lug and 1 wire lead Shelf Life: N/a	
0.086 inches single group Winding Operating Current: 640.0 milliamperes ac single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 1 tab, solder lug and 1 wire lead Shelf Life: N/a	
Winding Operating Current: 640.0 milliamperes ac single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 1 tab, solder lug and 1 wire lead Shelf Life: N/a	
640.0 milliamperes ac single component single winding <b>Thread Series Designator:</b> Unc single group <b>Terminal Type And Quantity:</b> 1 tab, solder lug and 1 wire lead <b>Shelf Life:</b> N/a	
Thread Series Designator: Unc single group Terminal Type And Quantity: 1 tab, solder lug and 1 wire lead Shelf Life: N/a	
Unc single group <b>Terminal Type And Quantity:</b> 1 tab, solder lug and 1 wire lead <b>Shelf Life:</b> N/a	
Terminal Type And Quantity: 1 tab, solder lug and 1 wire lead Shelf Life: N/a	
1 tab, solder lug and 1 wire lead <b>Shelf Life:</b> N/a	
Shelf Life: N/a	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A058b0	