

View Online at <https://aerobasegroup.com/nsn/5950-00-019-3012>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.484 inches single mounting facility single center group and 3.515 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.109 inches single mounting facility single center group and 2.140 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Three phase to three phase single component

**Transformer Winding Connection Type:**

Delta-wye

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

Between 4.515 inches and 4.546 inches

**Body Width:**

Between 2.984 inches and 3.015 inches

**Body Height:**

3.437 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thread Size:**

0.164 inches single group

**Criticality Code Justification:**

Feat

**Winding Operating Voltage:**

416.00 ac volts single component single primary

**Special Features:**

Must function in a liquid cooled power supply per fc 77

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

22 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0