NSN 5950-00-019-5915

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-019-5915

Thread Direction (non-core): Err-070 Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 0.800 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.060 inches single mounting facility single center group Overall Height: 1.750 inches Overall Width: 1.500 inches Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 1.690 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 0.800 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.060 inches single mounting facility single center group Overall Height: 1.750 inches Overall Width: 1.500 inches Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 1.690 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
Center To Center Distance Between Mounting Facilities Parallel To Length: 0.800 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.060 inches single mounting facility single center group Overall Height: 1.750 inches Overall Width: 1.500 inches Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 1.690 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
Center To Center Distance Between Mounting Facilities Parallel To Length: 0.800 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.060 inches single mounting facility single center group Overall Height: 1.750 inches Overall Width: 1.500 inches Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 1.690 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpl): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
Center To Center Distance Between Mounting Facilities Parallel To Width: 1.060 inches single mounting facility single center group Overall Height: 1.750 inches Overall Width: 1.500 inches Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 1.690 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
Center To Center Distance Between Mounting Facilities Parallel To Width: 1.060 inches single mounting facility single center group Overall Height: 1.750 inches Overall Width: 1.500 inches Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 1.690 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
1.060 inches single mounting facility single center group Overall Height: 1.750 inches Overall Width: 1.500 inches Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 1.690 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
Overall Height: 1.750 inches Overall Width: 1.500 inches Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 1.690 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
1.750 inches Overall Width: 1.500 inches Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 1.690 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
Overall Width: 1.500 inches Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 1.690 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
1.500 inches Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 1.690 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 1.690 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
Input-output Phase Relationship: Single phase to single phase single component Body Length: 1.690 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
Input-output Phase Relationship: Single phase to single phase single component Body Length: 1.690 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
Single phase to single phase single component Body Length: 1.690 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
Body Length: 1.690 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
Threaded hole single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:
32 single group Thread Size: 0.138 inches single group Winding Operating Current:
Thread Size: 0.138 inches single group Winding Operating Current:
0.138 inches single group Winding Operating Current:
Winding Operating Current:
1.5 amperes ac single component single secondary
Winding Operating Voltage:
10.00 ac volts and 26.00 ac volts single component single secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
5 solder stud
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5950-00-019-5915

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0