NSN 5950-00-020-2832

Radio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-020-2832

| Polichility Indicatory |
|--|
| Reliability Indicator: Not established |
| |
| Turn Quantity: |
| 45 single component all primary |
| Inductance Rating: |
| 2.00 microhenries single component all primary |
| Frequency Rating: |
| 18.0 megahertz single component |
| Coil Form Type: |
| Hollow single component |
| Adjustment Device Drive Type: |
| Slotted screw single component |
| Body Length: |
| 3.750 inches |
| Body Outside Diameter: |
| 0.250 inches |
| Inclosure Type: |
| Open |
| Mounting Facility Quantity: |
| 1 single group |
| Mounting Method: |
| Core single group and threaded stud single group |
| Rating Method: |
| Electrical single component all primary and winding turns single component all primary |
| Winding Function And Quantity: |
| 2 primary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.164 inches single group |
| Winding Conductor Size: |
| 0.01264 inches american wire gage single component all primary |
| Adjustment Method And Quantity: |
| 2 adjustable core single component |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 4 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 5950-00-020-2832

Radio Frequency Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0