

View Online at <https://aerobasegroup.com/nsn/5950-00-020-3336>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.281 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.281 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.500 inches

Body Width:

1.500 inches

Body Height:

2.312 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

55.0 milliamperes ac single component single secondary and 73.0 milliamperes ac single component single secondary and 83.0 milliamperes ac single component single secondary and 103.0 milliamperes ac single component single secondary and 115.0 milliamperes ac single component single secondary and 150.0 milliamperes ac single component single secondary

Winding Operating Voltage:

6.00 ac volts single component single secondary and 8.00 ac volts single component single secondary and 10.00 ac volts single component single secondary and 12.00 ac volts single component single secondary and 14.00 ac volts single component single secondary and 18.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 wire hook

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A058b0