

View Online at <https://aerobasegroup.com/nsn/5950-00-020-3336>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.281 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.281 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

1.500 inches

**Body Width:**

1.500 inches

**Body Height:**

2.312 inches

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

55.0 milliamperes ac single component single secondary and 73.0 milliamperes ac single component single secondary and 83.0 milliamperes ac single component single secondary and 103.0 milliamperes ac single component single secondary and 115.0 milliamperes ac single component single secondary and 150.0 milliamperes ac single component single secondary

**Winding Operating Voltage:**

6.00 ac volts single component single secondary and 8.00 ac volts single component single secondary and 10.00 ac volts single component single secondary and 12.00 ac volts single component single secondary and 14.00 ac volts single component single secondary and 18.00 ac volts single component single secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

10 wire hook

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fig:**

A058b0