

View Online at <https://aerobasegroup.com/nsn/5950-00-020-5143>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches single mounting facility single center group

Frequency Rating:

320.0 hertz single component and 1.76 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

Between 3.687 inches and 3.812 inches

Body Width:

Between 3.063 inches and 3.188 inches

Body Height:

Between 3.813 inches and 4.000 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Voltage:

795.00 ac volts single component 1st secondary and 1.09 ac kilovolts single component 1st secondary and 1.394 ac kilovolts single component 1st secondary and 1.689 ac kilovolts single component 1st secondary and 2.484 ac kilovolts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

15 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0