## NSN 5950-00-020-5143

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-020-5143

View Online at https://aerobasegroup.com/nsn/5950-00-020-5143	
Reliability Indicator:	
Not established	
Center To Center Distance Between Mounting Facilities Parallel To Length:	
3.000 inches single mounting facility single center group	
Center To Center Distance Between Mounting Facilities Parallel To Width:	
2.250 inches single mounting facility single center group	
Frequency Rating:	
320.0 hertz single component and 1.76 kilohertz single component	
Input-output Phase Relationship:	
Single phase to single phase single component	
Vinding Shielding Method:	
nternal shield grounded to inclosure single component	
Body Length:	
Between 3.687 inches and 3.812 inches	
Body Width:	
Between 3.063 inches and 3.188 inches	
Body Height:	
Between 3.813 inches and 4.000 inches	
nclosure Type:	
Hermetically sealed	
Mounting Facility Quantity:	
1 single group	
Nounting Method:	
Threaded stud single group	
Vinding Function And Quantity:	
primary single component and 4 secondary single component	
Thready Qty Per Inch (tpi):	
20 single group	
hread Size:	
0.250 inches single group	
Winding Operating Voltage:	
795.00 ac volts single component 1st secondary and 1.09 ac kilovolts single component 1st secondary and 1.394 ac kilovolts	single
component 1st secondary and 1.689 ac kilovolts single component 1st secondary and 2.484 ac kilovolts single component 1st	t secondary
Thread Series Designator:	
Jnc single group	
Terminal Type And Quantity:	
15 wire hook	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	

## NSN 5950-00-020-5143

Power Transformer - Page 2 of 2

**Fiig:** A058b0

