## NSN 5950-00-020-5795

Radio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-020-5795

Reliability Indicator:
Not established
Turn Quantity:
250 single component single primary
Inductance Rating:
170.00 microhenries single component single primary
Frequency Rating:
250.0 kilohertz single component
Coil Form Type:
Hollow single component
Adjustment Device Drive Type:
Slotted screw single component
Body Length:
1.250 inches
Body Width:
1.250 inches
Body Height:
1.188 inches
Distance Between Mounting Facility Centers:
0.937 inches single mounting facility single center group
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
2 single group  Mounting Method:
Mounting Method:
Mounting Method: Threaded stud single group
Mounting Method: Threaded stud single group Rating Method:
Mounting Method: Threaded stud single group Rating Method: Electrical single component single primary
Mounting Method: Threaded stud single group Rating Method: Electrical single component single primary Winding Function And Quantity:
Mounting Method: Threaded stud single group Rating Method: Electrical single component single primary Winding Function And Quantity: 1 primary single component and 1 secondary single component
Mounting Method: Threaded stud single group Rating Method: Electrical single component single primary Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi):
Mounting Method: Threaded stud single group Rating Method: Electrical single component single primary Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group
Mounting Method: Threaded stud single group Rating Method: Electrical single component single primary Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size:
Mounting Method: Threaded stud single group Rating Method: Electrical single component single primary Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group
Mounting Method: Threaded stud single group Rating Method: Electrical single component single primary Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Adjustment Method And Quantity:
Mounting Method: Threaded stud single group Rating Method: Electrical single component single primary Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Adjustment Method And Quantity: 1 adjustable core single component
Mounting Method: Threaded stud single group Rating Method: Electrical single component single primary Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator:
Mounting Method: Threaded stud single group Rating Method: Electrical single component single primary Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unc single group

N/a

## NSN 5950-00-020-5795

Radio Frequency Transformer - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A058b0