

View Online at <https://aerobasegroup.com/nsn/5950-00-021-6923>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.125 inches single mounting facility single center group

Mounting Slot Width:

0.297 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

100.0 volt-ampere single component

Body Length:

Between 6.740 inches and 6.760 inches

Body Width:

4.000 inches

Body Height:

4.000 inches

Maximum Operating Temp:

125.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

3 single group

Mounting Method:

Flange single group and slot single group

Cooling Method:

Self-cooled

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Center To Center Distance Between Mounting Facilities Parallel To The Base Of An Isosceles Triangle:

3.115 inches single mounting facility single center group and 3.135 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

5.865 inches single mounting facility single center group and 5.885 inches single mounting facility single center group

Winding Operating Voltage:

440.00 ac volts single component single primary

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0