NSN 5950-00-024-1000

Current Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-024-1000

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

9.970 inches single mounting facility single center group and 10.070 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.340 inches single mounting facility single center group and 2.410 inches single mounting facility single center group

Mounting Hole Diameter:

0.520 inches single group

Mounting Slot Width:

0.106 inches single group

Frequency Rating:

50.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

25.0 volt-ampere single component

Body Length:

Between 10.600 inches and 10.700 inches

Body Width:

Between 2.820 inches and 2.920 inches

Body Height:

Between 3.700 inches and 3.800 inches

Installation For Which Designed:

Indoor nonportable

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

6 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

3 secondary single component

Winding Operating Current:

1.0 amperes ac single component all secondary

Winding Operating Voltage:

10.00 ac volts single component all primary

Special Features:

Primaries rated but not included

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

NSN 5950-00-024-1000

Current Transformer - Page 2 of 2



		• .					
	In	iŧ	Of	MAG	200		ω.
•	,,,	ıL	v.	IAIC	as	u	┏.

--

Demilitarization:

No

Fiig:

A058b0