

View Online at <https://aerobasegroup.com/nsn/5950-00-027-2452>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Two phase to two phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

3.562 inches

Body Width:

3.062 inches

Body Height:

4.875 inches

End Application:

Arsr-1, ca-4039 power supply

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

4.5 amperes ac single component 2nd secondary

Winding Operating Voltage:

6.30 ac volts single component 2nd secondary

Special Features:

Function, transformer, power, step down and step up; reference data, ps5301t2, instruction book, arsr-1d/e/f, vol 5 sec 10, pg 10-184

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0