

View Online at <https://aerobasegroup.com/nsn/5950-00-027-5307>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.750 inches all mounting facilities all center groupings

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.437 inches all mounting facilities all center groupings

**Impedance Rating In Ohms:**

500.0 single component 2nd secondary

**Body Length:**

2.625 inches

**Body Width:**

2.375 inches

**Body Height:**

3.625 inches

**End Application:**

Arsr-1, fa-4154 blocking oscillator, arsr-2, fa-7114 blocking oscillator

**Inclosure Type:**

Hermetically sealed with oil

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Thread Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.164 inches single group

**Winding Operating Current:**

250.0 milliamperes ac single component 1st secondary

**Special Features:**

T-7502, instruction book arsr-1d/e/f, vol 5, sec 10, pg 10-751; t-7502, instruction book arsr-2, vol 5, sec 10, pg 10-555

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0