

View Online at <https://aerobasegroup.com/nsn/5950-00-027-5307>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.750 inches all mounting facilities all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.437 inches all mounting facilities all center groupings

Impedance Rating In Ohms:

500.0 single component 2nd secondary

Body Length:

2.625 inches

Body Width:

2.375 inches

Body Height:

3.625 inches

End Application:

Arsr-1, fa-4154 blocking oscillator, arsr-2, fa-7114 blocking oscillator

Inclosure Type:

Hermetically sealed with oil

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

250.0 milliamperes ac single component 1st secondary

Special Features:

T-7502, instruction book arsr-1d/e/f, vol 5, sec 10, pg 10-751; t-7502, instruction book arsr-2, vol 5, sec 10, pg 10-555

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0