# NSN 5950-00-030-9009

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-030-9009

# Reliability Indicator:

Not established

# Center To Center Distance Between Mounting Facilities Parallel To Length:

3.980 inches single mounting facility single center group and 4.020 inches single mounting facility single center group

# Center To Center Distance Between Mounting Facilities Parallel To Width:

2.730 inches single mounting facility single center group and 2.770 inches single mounting facility single center group

# **Overall Height:**

Between 7.430 inches and 7.940 inches

## **Frequency Rating:**

400.0 hertz single component

# Input-output Phase Relationship:

Three phase to three phase single component

# Transformer Winding Connection Type:

Delta-wye

### Winding Shielding Method:

Core grounded single component and internal shield brought out to terminal single component

### **Body Length:**

Between 4.750 inches and 4.880 inches

### Body Width:

Between 3.880 inches and 4.000 inches

## **Body Height:**

Between 6.310 inches and 6.500 inches

## Maximum Operating Temp:

130.0 degrees celsius

### Inclosure Type:

Fully enclosed

## **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded stud single group

## Winding Function And Quantity:

1 primary single component and 2 secondary single component

#### **Thread Size:**

0.250 inches single group

## Winding Operating Current:

370.0 milliamperes ac single component 2nd secondary

## Winding Operating Voltage:

520.00 ac volts single component 1st secondary

#### **Thread Series Designator:**

Unc single group

#### Terminal Type And Quantity:

16 standoff, threaded stud

# NSN 5950-00-030-9009

Power Transformer - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0

