

View Online at <https://aerobasegroup.com/nsn/5950-00-033-7622>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.802 inches single mounting facility single center group and 0.822 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.490 inches single mounting facility single center group and 0.510 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internally shielded single component

Body Length:

Between 1.296 inches and 1.328 inches

Body Width:

Between 0.990 inches and 1.010 inches

Body Height:

Between 0.990 inches and 1.010 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

30.0 milliamperes dc single component single primary

Winding Operating Voltage:

30.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0