

View Online at <https://aerobasegroup.com/nsn/5950-00-034-0946>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.188 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Mounting Hole Diameter:

0.173 inches single group

Frequency Rating:

47.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

External inclosure single component

Body Length:

2.688 inches

Body Width:

2.313 inches

Body Height:

2.250 inches

Maximum Operating Temp:

160.0 degrees fahrenheit

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

0.88 amperes ac single component single secondary and 0.94 amperes ac single component single secondary

Winding Operating Voltage:

5.00 ac volts single component single secondary and 5.50 ac volts single component single secondary

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0