NSN 5950-00-034-1090

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-034-1090

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.938 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.125 inches single mounting facility single center group |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Three phase to three phase single component |
| Body Length: |
| 3.562 inches |
| Body Width: |
| 1.750 inches |
| Body Height: |
| 3.125 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 3 secondary single component |
| Thread Size: |
| 0.190 inches single group |
| Winding Operating Current: |
| 250.0 milliamperes dc single component 3rd secondary |
| Winding Operating Voltage: |
| 250.00 dc volts single component 2nd secondary |
| Thread Series Designator: |
| Unf single group |
| Terminal Type And Quantity: |
| 13 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

Fiig:

A058b0