## NSN 5950-00-041-6527

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-041-6527

| View Online at https://aerobasegroup.com/nsn/5950-00-041-6527  |
|--|
| Reliability Indicator:   |
| Not established  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:                                    |
| 3.000 inches single mounting facility single center group  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:                                     |
| 2.000 inches single mounting facility single center group  |
| Overall Height:  |
| 4.625 inches   |
| Frequency Rating:  |
| 400.0 hertz single component   |
| Input-output Phase Relationship:   |
| Three phase to three phase single component  |
| Winding Shielding Method:  |
| Internal shield brought out to terminal single component and ground brought out to terminal single component |
| Body Length:   |
| 4.500 inches   |
| Body Width:  |
| 2.625 inches   |
| Body Height:   |
| 4.000 inches   |
| Inclosure Type:  |
| Partially enclosed, double shell   |
| Mounting Facility Quantity:  |
| 4 single group   |
| Mounting Method:   |
| Threaded stud single group   |
| Winding Function And Quantity:   |
| 1 primary single component and 1 secondary single component  |
| Thready Qty Per Inch (tpi):  |
| 32 single group  |
| Thread Size:   |
| 0.164 inches single group  |
| Winding Operating Voltage:   |
| 27.00 ac volts single component single secondary   |
| Thread Series Designator:  |
| Unc single group   |
| Terminal Type And Quantity:  |
| 9 tab, solder lug  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 5950-00-041-6527

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0