# NSN 5950-00-041-6535

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-041-6535

# **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.837 inches single mounting facility single center group and 3.062 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.500 inches single mounting facility single center group and 2.625 inches single mounting facility single center group

#### **Overall Height:**

Between 5.437 inches and 5.625 inches

#### **Frequency Rating:**

400.0 hertz single component

#### Input-output Phase Relationship:

Three phase to three phase single component

#### **Transformer Winding Connection Type:**

Wye-wye

#### **Winding Shielding Method:**

Internal shield brought out to terminal single component and ground brought out to terminal single component

#### **Body Length:**

Between 2.837 inches and 3.062 inches

#### **Body Width:**

Between 2.500 inches and 2.625 inches

# **Body Height:**

Between 4.062 inches and 4.250 inches

#### **Maximum Operating Temp:**

65.0 degrees celsius

# **Inclosure Type:**

Hermetically sealed

# **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded stud single group

# Winding Function And Quantity:

1 primary single component and 2 secondary single component

# Thread Size:

0.164 inches single group

# **Winding Operating Current:**

2.0 amperes dc single component all secondary

# **Winding Operating Voltage:**

23.00 ac volts single component 1st secondary

# **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

11 threaded stud

# NSN 5950-00-041-6535

Power Transformer - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0