

View Online at <https://aerobasegroup.com/nsn/5950-00-041-6535>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.837 inches single mounting facility single center group and 3.062 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group and 2.625 inches single mounting facility single center group

Overall Height:

Between 5.437 inches and 5.625 inches

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-wye

Winding Shielding Method:

Internal shield brought out to terminal single component and ground brought out to terminal single component

Body Length:

Between 2.837 inches and 3.062 inches

Body Width:

Between 2.500 inches and 2.625 inches

Body Height:

Between 4.062 inches and 4.250 inches

Maximum Operating Temp:

65.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

2.0 amperes dc single component all secondary

Winding Operating Voltage:

23.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

11 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0