

View Online at <https://aerobasegroup.com/nsn/5950-00-041-6554>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.683 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.533 inches single mounting facility single center group

Overall Height:

1.100 inches

Mounting Hole Diameter:

0.123 inches single group and 0.134 inches single group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core and brought out to terminal single component

Body Length:

0.870 inches

Body Width:

0.780 inches

Body Height:

0.740 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

0.4 amperes ac single component single secondary

Winding Operating Voltage:

5.00 ac pounds per hour wet single component single secondary

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0