

View Online at <https://aerobasegroup.com/nsn/5950-00-043-2615>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group

Frequency Rating:

47.5 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

3.562 inches

Body Width:

3.062 inches

Body Height:

4.875 inches

End Application:

Wsd: mars class t-afs 1; whidbey island class lsd; emory s. Land class as; ticonderoga class cg (47); supply class aoe; powhatan class t-atf 166

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

250.0 milliamperes ac single component 1st secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

57.00 ac volts single component single primary

Special Features:

Weapon system essential

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0