# NSN 5950-00-044-2295

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-044-2295

# Reliability Indicator:

Not established

# Center To Center Distance Between Mounting Facilities Parallel To Length:

6.120 inches single mounting facility single center group

# Center To Center Distance Between Mounting Facilities Parallel To Width:

4.380 inches single mounting facility single center group

#### **Overall Height:**

8.690 inches

#### **Frequency Rating:**

59.0 hertz single component and 61.0 hertz single component

### Input-output Phase Relationship:

Three phase to three phase single component

#### **Transformer Winding Connection Type:**

Wye-delta

#### Winding Shielding Method:

Internal shield grounded to inclosure single component

#### **Body Length:**

7.030 inches

#### Body Width:

5.310 inches

#### **Body Height:**

7.940 inches

#### Maximum Operating Temp:

105.0 degrees celsius

#### Inclosure Type:

Hermetically sealed

#### **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded stud single group

#### Winding Function And Quantity:

1 primary single component and 1 secondary single component

#### Thready Qty Per Inch (tpi):

20 single group

#### **Thread Size:**

0.250 inches single group

#### Winding Operating Current:

35.0 amperes ac single component single secondary

### Winding Operating Voltage:

6.25 ac volts single component single secondary

# **Thread Series Designator:**

Unc single group

# NSN 5950-00-044-2295

Power Transformer - Page 2 of 2



# Terminal Type And Quantity:

18 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0