## NSN 5950-00-046-5589

Power Transformer - Page 1 of 2

Reliability Indicator:



View Online at https://aerobasegroup.com/nsn/5950-00-046-5589

Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.500 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.875 inches single mounting facility single center group
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to core single component
Body Length:
1.700 inches
Body Width:
2.300 inches
Body Height:
2.620 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and threaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thread Size:
0.138 inches single group
Winding Operating Current:
3.5 amperes ac single component single secondary
Winding Operating Voltage:
9.00 ac volts single component single secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

## NSN 5950-00-046-5589

Power Transformer - Page 2 of 2



Fiig:

A058b0