

View Online at <https://aerobasegroup.com/nsn/5950-00-049-3804>

**Reliability Indicator:**

Not established

**Mounting Hole Diameter:**

0.164 inches single group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

2.500 inches

**Body Width:**

2.188 inches

**Body Height:**

2.688 inches

**Distance Between Mounting Facility Centers:**

1.406 inches single mounting facility single center group and 1.938 inches single mounting facility single center group

**End Application:**

Jwsd: nimitz class cvn; Forrestal cv; ticonderoga cg (47); Arleigh Burke ddg; Oliver Perry ffg; supply aoe; wasp lhd; Kidd ddg; Spruance dd (963); Virginia CGN (41); Austin ship lpd-4 amphibious transport docks

**Inclosure Type:**

Partially enclosed, double shell

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Operating Current:**

1.0 amperes ac single component single secondary

**Winding Power Rating:**

15.0 volts-amperes single component single secondary

**Criticality Code Justification:**

Feat

**Winding Operating Voltage:**

6.85 ac volts single component single secondary

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

2 binding post and 2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0