

View Online at <https://aerobasegroup.com/nsn/5950-00-049-3804>

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.164 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.500 inches

Body Width:

2.188 inches

Body Height:

2.688 inches

Distance Between Mounting Facility Centers:

1.406 inches single mounting facility single center group and 1.938 inches single mounting facility single center group

End Application:

Jwsd: nimitz class cvn; Forrestal cv; ticonderoga cg (47); Arleigh Burke ddg; Oliver Perry ffg; supply aoe; wasp lhd; Kidd ddg; Spruance dd (963); Virginia CGN (41); Austin ship lpd-4 amphibious transport docks

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

1.0 amperes ac single component single secondary

Winding Power Rating:

15.0 volts-amperes single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

6.85 ac volts single component single secondary

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 binding post and 2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0