NSN 5950-00-051-0004

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-051-0004

Reliability Ind	icator:
-----------------	---------

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.810 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

2.820 inches

Body Width:

3.400 inches

Body Height:

4.500 inches

Inclosure Type:

Partially enclosed, half shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

3.1 amperes ac single component 3rd secondary

Winding Operating Voltage:

6.30 ac volts single component 3rd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

13 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5950-00-051-0004

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0