NSN 5950-00-052-4283

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-052-4283

| Reliability Indicator: |
|---|
| Not established |
| Overall Length: |
| 1.690 inches |
| Overall Width: |
| 1.160 inches |
| Frequency Rating: |
| 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield brought out to terminal single component |
| Body Length: |
| 1.690 inches |
| Body Width: |
| 1.160 inches |
| Body Height: |
| 1.180 inches |
| Distance Between Mounting Facility Centers: |
| 1.312 inches single mounting facility single center group |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 2 single group |
| Mounting Method: |
| Flange single group and threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 3.0 milliamperes ac single component all secondary |
| Winding Operating Voltage: |
| 22.40 ac volts single component all secondary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 7 solder stud |
| Shelf Life: |
| N/a |

NSN 5950-00-052-4283Power Transformer - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

Demilitarization:

No

Fiig:

A058b0