

View Online at <https://aerobasegroup.com/nsn/5950-00-052-9029>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.980 inches single mounting facility single center group and 3.020 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.640 inches single mounting facility single center group and 2.680 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

4.875 inches

Body Width:

3.875 inches

Body Height:

6.125 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

650.0 milliamperes dc single component single secondary and 1.15 amperes dc single component single secondary

Winding Power Rating:

80.0 volts-amperes single component single secondary

Winding Operating Voltage:

69.50 dc volts single component single secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0