

View Online at <https://aerobasegroup.com/nsn/5950-00-053-1569>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.865 inches single mounting facility single center group and 0.885 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.865 inches single mounting facility single center group and 0.885 inches single mounting facility single center group

Frequency Rating:

5.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.280 inches

Body Width:

1.125 inches

Body Height:

1.280 inches

Maximum Operating Temp:

75.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

3 primary single component and 2 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

500.0 milliamperes dc single component 1st secondary

Winding Operating Voltage:

8.50 dc volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

12 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0