# NSN 5950-00-054-2226

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-054-2226

# **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.750 inches single mounting facility single center group

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

2.750 inches single mounting facility single center group

#### **Overall Height:**

5.500 inches

#### **Frequency Rating:**

400.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield grounded to inclosure single component

#### **Body Length:**

3.875 inches

#### **Body Width:**

3.875 inches

#### **Body Height:**

4.875 inches

# **Maximum Operating Temp:**

65.0 degrees celsius

#### **Inclosure Type:**

Hermetically sealed

## **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Threaded stud single group

#### **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

## Thready Qty Per Inch (tpi):

20 single group

#### Thread Size:

0.250 inches single group

#### **Winding Operating Current:**

9.0 amperes ac single component single secondary

# **Winding Operating Voltage:**

62.00 ac volts single component single secondary

# **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

7 tab, solder lug

# NSN 5950-00-054-2226

Power Transformer - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0