

View Online at <https://aerobasegroup.com/nsn/5950-00-055-5091>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.562 inches single mounting facility single center group

Frequency Rating:

47.5 hertz single component and 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

3.313 inches

Body Width:

3.250 inches

Body Height:

3.625 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

60.0 milliamperes ac single component 4th secondary

Winding Power Rating:

75.0 volts-amperes single component single primary

Winding Operating Voltage:

97.00 ac volts single component single primary and 113.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0