Radio Frequency Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-055-6136

Reliability Indicator: Not established Inductance Rating: 0.147 microhenries single component single primary Coil Form Type: Hollow single component Adjustment Device Drive Type: Shaft single component Body Length: 0.750 inches Body Outside Diameter: 0.375 inches Inclosure Type: Open Mounting Method: Threaded bushing single group Winding Function And Quantity: 1 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group
Inductance Rating: 0.147 microhenries single component single primary Coil Form Type: Hollow single component Adjustment Device Drive Type: Shaft single component Body Length: 0.750 inches Body Outside Diameter: 0.375 inches Inclosure Type: Open Mounting Method: Threaded bushing single group Winding Function And Quantity: 1 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group
0.147 microhenries single component single primary Coil Form Type: Hollow single component Adjustment Device Drive Type: Shaft single component Body Length: 0.750 inches Body Outside Diameter: 0.375 inches Inclosure Type: 0.375 inches Inclosure Type: Open Mounting Method: Threaded bushing single group Winding Function And Quantity: 1 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group
Coil Form Type: Hollow single component Adjustment Device Drive Type: Shaft single component Body Length: 0.750 inches Body Outside Diameter: 0.375 inches Inclosure Type: Open Mounting Method: Threaded bushing single group Winding Function And Quantity: 1 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group
Hollow single componentAdjustment Device Drive Type:Shaft single componentBody Length:0.750 inchesBody Outside Diameter:0.375 inchesInclosure Type:OpenMounting Method:Threaded bushing single groupWinding Function And Quantity:1 primary single componentThready Qty Per Inch (tpi):32 single groupThread Size:0.190 inches single groupAdjustment Method And Quantity:1 adjustable core single componentThread Size:0.190 inches single groupAdjustment Method And Quantity:1 adjustable core single componentThread Series Designator:Unf single group
Adjustment Device Drive Type: Shaft single component Body Length: 0.750 inches Body Outside Diameter: 0.375 inches Inclosure Type: Open Mounting Method: Threaded bushing single group Winding Function And Quantity: 1 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group
Shaft single component Body Length: 0.750 inches Body Outside Diameter: 0.375 inches Inclosure Type: Open Mounting Method: Threaded bushing single group Winding Function And Quantity: 1 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group
Body Length: 0.750 inches Body Outside Diameter: 0.375 inches Inclosure Type: Open Mounting Method: Threaded bushing single group Winding Function And Quantity: 1 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group
0.750 inches Body Outside Diameter: 0.375 inches Inclosure Type: Open Mounting Method: Threaded bushing single group Winding Function And Quantity: 1 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group
Body Outside Diameter: 0.375 inches Inclosure Type: Open Mounting Method: Threaded bushing single group Winding Function And Quantity: 1 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group
0.375 inches Inclosure Type: Open Mounting Method: Threaded bushing single group Winding Function And Quantity: 1 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group
Inclosure Type: Open Mounting Method: Threaded bushing single group Winding Function And Quantity: 1 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group
Open Mounting Method: Threaded bushing single group Winding Function And Quantity: 1 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group
Mounting Method: Threaded bushing single group Winding Function And Quantity: 1 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group
Threaded bushing single group Winding Function And Quantity: 1 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group
Winding Function And Quantity: 1 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group
<ol> <li>primary single component</li> <li>Thready Qty Per Inch (tpi):</li> <li>32 single group</li> <li>Thread Size:</li> <li>0.190 inches single group</li> <li>Adjustment Method And Quantity:</li> <li>1 adjustable core single component</li> <li>Thread Series Designator:</li> <li>Unf single group</li> </ol>
Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group
32 single group Thread Size: 0.190 inches single group Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group
Thread Size: 0.190 inches single group Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group
0.190 inches single group Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group
Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group
1 adjustable core single component Thread Series Designator: Unf single group
Thread Series Designator: Unf single group
Unf single group
Terminal Type And Quantity:
Terminar Type And Quantity.
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A058b0