NSN 5950-00-056-8284

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-056-8284

| Re | eliability Indicator: |
|-----|--|
| No | ot established |
| Ce | enter To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.0 | 625 inches single mounting facility single center group |
| Ce | enter To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.0 | 625 inches single mounting facility single center group |
| Fr | equency Rating: |
| 50 | 0.0 hertz single component or 60.0 hertz single component |
| In | put-output Phase Relationship: |
| Si | ngle phase to single phase single component |
| Bo | ody Length: |
| 3. | 560 inches |
| Bo | ody Width: |
| 1.(| 620 inches |
| Bo | ody Height: |
| 3.8 | 870 inches |
| Ma | aximum Operating Temp: |
| 10 | 5.0 degrees celsius |
| In | closure Type: |
| Fι | Illy enclosed |
| M | ounting Facility Quantity: |
| 4 : | single group |
| M | ounting Method: |
| Th | nreaded stud single group |
| w | inding Function And Quantity: |
| 1 | primary single component and 1 secondary single component |
| Tŀ | nread Size: |
| 0. | 164 inches single group |
| w | inding Operating Current: |
| 2.(| 0 amperes ac single component single secondary |
| w | inding Operating Voltage: |
| 25 | 5.20 ac volts single component single secondary |
| Tŀ | nread Series Designator: |
| Ur | nc single group |
| Те | erminal Type And Quantity: |
| 41 | tab, solder lug |
| Sł | nelf Life: |
| N/ | a |
| Ur | nit Of Measure: |
| | |
| De | emilitarization: |
| |) |

NSN 5950-00-056-8284 Power Transformer - Page 2 of 2

Fiig: A058b0

