NSN 5950-00-057-0777

Radio Frequency Coil - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-057-0777

Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Fungus resistant and moisture resistant
Inductance Rating:
10.00 millihenries single component single winding
Coil Form Type:
Solid single component
Core Construction:
S0lid single component
Body Length:
0.375 inches
Overall Diameter:
0.335 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Terminal single group
Rating Method:
3 - 1 - 1 - 1
Electrical single component single winding
Electrical single component single winding
Electrical single component single winding Winding Operating Current:
Electrical single component single winding Winding Operating Current: 38.0 milliamperes dc single component single winding
Electrical single component single winding Winding Operating Current: 38.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms:
Electrical single component single winding Winding Operating Current: 38.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 101.000 single component single winding
Electrical single component single winding Winding Operating Current: 38.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 101.000 single component single winding Quality Factor:
Electrical single component single winding Winding Operating Current: 38.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 101.000 single component single winding Quality Factor: 41 single component single winding
Electrical single component single winding Winding Operating Current: 38.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 101.000 single component single winding Quality Factor: 41 single component single winding Terminal Type And Quantity:
Electrical single component single winding Winding Operating Current: 38.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 101.000 single component single winding Quality Factor: 41 single component single winding Terminal Type And Quantity: 2 wire lead
Electrical single component single winding Winding Operating Current: 38.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 101.000 single component single winding Quality Factor: 41 single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life:
Electrical single component single winding Winding Operating Current: 38.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 101.000 single component single winding Quality Factor: 41 single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Electrical single component single winding Winding Operating Current: 38.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 101.000 single component single winding Quality Factor: 41 single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Electrical single component single winding Winding Operating Current: 38.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 101.000 single component single winding Quality Factor: 41 single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:
Electrical single component single winding Winding Operating Current: 38.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 101.000 single component single winding Quality Factor: 41 single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization:
Electrical single component single winding Winding Operating Current: 38.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 101.000 single component single winding Quality Factor: 41 single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No