

View Online at <https://aerobasegroup.com/nsn/5950-00-058-6372>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.312 inches single mounting facility single center group

Mounting Slot Width:

0.188 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.250 inches

Body Width:

3.500 inches

Body Height:

3.938 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Voltage:

40.00 ac volts single component single primary and 85.00 ac volts single component single primary and 117.00 ac volts single component single primary and 180.00 ac volts single component single primary

Test Data Document:

62133-2-13297 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

8 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0