

View Online at <https://aerobasegroup.com/nsn/5950-00-059-2899>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Mounting Slot Width:

0.203 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

3.750 inches

Body Width:

3.313 inches

Body Height:

4.000 inches

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Winding Operating Current:

4.0 amperes ac single component 2nd secondary

Winding Operating Voltage:

29.70 ac volts single component 3rd secondary and 46.00 ac volts single component 3rd secondary

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0