# NSN 5950-00-059-3010

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-059-3010

# **Reliability Indicator:**

Not established

# Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches single mounting facility single center group

# Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

#### **Overall Height:**

Between 3.937 inches and 4.249 inches

#### Frequency Rating:

60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield grounded to inclosure single component

#### **Body Length:**

Between 2.625 inches and 2.750 inches

#### **Body Width:**

Between 2.250 inches and 2.375 inches

#### **Body Height:**

Between 3.624 inches and 3.812 inches

# **Maximum Operating Temp:**

105.0 degrees celsius

#### **Inclosure Type:**

Hermetically sealed

# **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Threaded stud single group

#### **Winding Function And Quantity:**

1 primary single component and 2 secondary single component

# Thready Qty Per Inch (tpi):

32 single group

# **Thread Size:**

0.164 inches single group

# **Winding Operating Current:**

500.0 milliamperes ac single component 1st secondary

# **Winding Operating Voltage:**

65.00 ac volts single component single primary

# **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

8 solder stud

# NSN 5950-00-059-3010

Power Transformer - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0