## NSN 5950-00-060-3039

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-060-3039

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.750 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.750 inches single mounting facility single center group
Mounting Slot Width:
0.250 inches single group
Inductance Type:
Fixed
Inductance Rating:
$5.75 \ \text{microhenries} \ \ \text{single component single winding and } 38.00 \ \text{microhenries} \ \ \text{single component single winding}$
Frequency Rating:
60.0 hertz single component or 400.0 hertz single component
Body Length:
4.562 inches
Body Width:
3.875 inches
Body Height:
5.375 inches
Maximum Operating Temp:
125.0 degrees fahrenheit
Winding Quantity:
1 single component
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and slot single group
Rating Method:
Electrical single component single winding
Winding Operating Current:
8.3 amperes ac single component single winding
Terminal Type And Quantity:
3 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5950-00-060-3039

Reactor - Page 2 of 2



Fiig:

A058b0