## NSN 5950-00-060-9143

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-060-9143

| Reliability Indicator:                                      |
|---|
| Not established   |
| Mounting Hole Diameter:                                     |
| 0.201 inches single group                                   |
| Frequency Rating:   |
| 400.0 hertz single component                                |
| Input-output Phase Relationship:                            |
| Single phase to single phase single component               |
| Body Length:  |
| 2.500 inches  |
| Body Width:   |
| 2.000 inches  |
| Body Height:  |
| 2.000 inches  |
| Maximum Operating Temp:                                     |
| 95.0 degrees fahrenheit                                     |
| Distance Between Mounting Facility Centers:                 |
| 1.875 inches single mounting facility single center group   |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:                                 |
| 2 single group  |
| Mounting Method:  |
| Unthreaded hole single group                                |
| Winding Function And Quantity:                              |
| 1 primary single component and 5 secondary single component |
| Winding Operating Current:                                  |
| 7.5 amperes ac single component 1st secondary               |
| Winding Operating Voltage:                                  |
| 6.30 ac volts single component 2nd secondary                |
| Special Features:   |
| 1primary and 5secondaries                                   |
| Terminal Type And Quantity:                                 |
| 14 turret   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |

ı ııg.

A058b0