## NSN 5950-00-061-5518

Current Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-061-5518

| Reliability Indicator:                                                    |
|---------------------------------------------------------------------------|
| Not established                                                           |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.750 inches single mounting facility single center group                 |
|                                                                           |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 2.500 inches single mounting facility single center group                 |
| Frequency Rating:                                                         |
| 60.0 hertz single component                                               |
| Input-output Phase Relationship:                                          |
| Single phase to single phase single component                             |
| Body Length:                                                              |
| 4.750 inches                                                              |
| Body Width:                                                               |
| 4.500 inches                                                              |
| Body Height:                                                              |
| 3.812 inches                                                              |
| Installation For Which Designed:                                          |
| Indoor nonportable                                                        |
| Inclosure Type:                                                           |
| Open                                                                      |
| Mounting Facility Quantity:                                               |
| 4 single group                                                            |
| Mounting Method:                                                          |
| Flange and unthreaded hole single group                                   |
| Winding Function And Quantity:                                            |
| 1 primary and 1 secondary single component                                |
| Winding Operating Current:                                                |
| 435.0 milliamperes ac single component single primary                     |
| Winding Operating Voltage:                                                |
| 460.00 ac volts single component single primary                           |
| Terminal Type And Quantity:                                               |
| 4 threaded stud                                                           |
| Shelf Life:                                                               |
| N/a                                                                       |
| Unit Of Measure:                                                          |
|                                                                           |
| Demilitarization:                                                         |
| No                                                                        |
| Fiig:                                                                     |
| A058b0                                                                    |
|                                                                           |
|                                                                           |