

View Online at <https://aerobasegroup.com/nsn/5950-00-062-1122>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.125 inches single mounting facility single center group

Mounting Slot Width:

0.250 inches single group

Frequency Rating:

50.0 hertz single component and 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

5.375 inches

Body Width:

4.562 inches

Body Height:

5.625 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

2 primary single component and 5 secondary single component

Winding Operating Current:

150.0 milliamperes dc single component 4th secondary and 210.00 milliamperes dc single component 4th secondary

Winding Operating Voltage:

275.00 dc volts single component 4th secondary

Special Features:

2 primary windings; 5 secondary windings; voltage and current have been rectified; terminal 12 is not used

Terminal Type And Quantity:

17 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0