

View Online at <https://aerobasegroup.com/nsn/5950-00-062-1146>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Mounting Hole Diameter:

0.218 inches single group

Frequency Rating:

50.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

4.000 inches

Body Width:

3.438 inches

Body Height:

3.938 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 8 secondary single component

Winding Operating Current:

3.0 amperes ac single component 3rd secondary

Winding Operating Voltage:

6.00 ac volts single component 3rd secondary

Special Features:

8 secondaries

Terminal Type And Quantity:

26 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0