

View Online at <https://aerobasegroup.com/nsn/5950-00-062-1499>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

6.690 inches all mounting facilities single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

5.420 inches all mounting facilities single center group and 5.460 inches all mounting facilities single center group

**Overall Height:**

7.310 inches

**Inductance Rating:**

0.80 millihenries 2nd component single winding

**Frequency Rating:**

360.0 hertz 1st component and 440.0 hertz 1st component

**Input-output Phase Relationship:**

Three phase to three phase 1st component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

7.920 inches

**Body Width:**

6.650 inches

**Maximum Operating Temp:**

105.0 degrees celsius

**Inclosure Type:**

Hermetically sealed with oil

**Mounting Facility Quantity:**

8 all groupings

**Mounting Method:**

Threaded hole all groupings

**Rating Method:**

Electrical 2nd component single winding

**Winding Function And Quantity:**

1 primary 1st component and 1 secondary 1st component

**Thready Qty Per Inch (tpi):**

20 all groupings

**Thread Size:**

0.250 inches all groupings

**Winding Operating Current:**

60.5 amperes ac 1st component single secondary

**Dc Resistance Rating In Ohms:**

0.006 2nd component single winding

**Winding Operating Voltage:**

120.00 ac pounds per hour wet 1st component single primary or 208.00 ac pounds per hour wet 1st component single primary

**Thread Series Designator:**

Unc all groupings

**Terminal Type And Quantity:**

11 standoff, threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0