

View Online at <https://aerobasegroup.com/nsn/5950-00-062-6099>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.562 inches single mounting facility single center group

Mounting Hole Diameter:

0.140 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.625 inches

Body Width:

2.625 inches

Body Height:

3.188 inches

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

40.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

5.00 ac volts single component 2nd secondary and 11.30 ac volts single component 2nd secondary

Terminal Type And Quantity:

9 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0